



# CatWalk / ClearWalk

CREATIVE ADVERTISING ON INDOOR FLOORS AND WET AREAS

CatWalk & ClearWalk can be used for short- and medium-term applications. CatWalk consists of an opaque floor graphic material that will make any image leap off the ground! ClearWalk is a translucent floor graphic material that blends with the surrounding surface creating unique and dynamic visual effects. The reverse side is coated with a pressure sensitive adhesive, which can be applied indoors on various surfaces and remains easily removable, without residue, even after long use. CatWalk & ClearWalk provide an extremely secure, slip-resistant and chemical resistance surface. Moreover, the quick and easily portable product is extremely foot friendly. The waterproof adhesive and associated durability of the film guarantee versatile usability. CatWalk & ClearWalk are ASTM D-2047 certified and meets the Euro-Norm as DIN/EN.

## Uses

- Can be used indoor on almost every surfaces tiles, marble, concrete, linoleum, porcelain, vinyl...
- Point-of-Purchase, Point-of-Sale
- Supermarkets, shopping malls,
- Fast food
- Pharmacies
- Museums
- Showers, bathtubs, wet areas - even inside pools
- Sauna

## Features & Benefits

- Lasts **up to 3 months**
- Is applicable on smooth **indoor & wet surfaces**
- **Tolerates water** in showers, swimming pools, etc. (applied dry)
- **Extremely secure** with its slip-resistant surface
- Impressive 3D effects
- CatWalk & ClearWalk can be cut with a normal cutting plotter
- Very robust, yet easily removable
- **Good chemical resistance** - anti bacteria treated
- **No Lamination, No Sandwich Structure!**
- Print and Apply
- **CatWalk** is a **white opaque** anti-slip material
- **ClearWalk** is a **transparent** anti-slip material



Shown on ClearWalk



Shown on CatWalk

sales@asphaltartusa.com  
www.asphaltartusa.com





# CatWalk / ClearWalk

CREATIVE ADVERTISING ON INDOOR FLOORS AND WET AREAS

## Printing & Application

CatWalk & ClearWalk are ink jet printable via: solvent, eco-solvent, UV or Latex inks. Application surface must be dry, clean and above 50°F before application.

## Durability

CatWalk & ClearWalk will last up to 3 months for indoor or wet area applications. The durability depends on proper application, the condition of the surface and the frequency of usage.

## Storage

It is recommended to store the product in closed packaging at a temperature of +60°F to +85°F (+15°C to +30°C) and humidity range of 45% to 60%. The product has a shelf life of 24 months.

## Warranty

Asphalt Art products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the Technical Specifications Sheets. Asphalt Art will replace or refund the price of any Asphalt Art materials found to not meet our product specifications. In no case shall Asphalt Art be liable for any direct, indirect, or consequential damages, including labor or non-Asphalt Art materials charges.

## Technical information

Roll Sizes:	51"x33' & 51"x100' (1.3m x 10m & 1.3m x 30m)
Thickness:	18mil (.457mm) + 2mil (.051mm) clear adhesive + 7mil (.178mm) liner
Slip-Resistance Certifications:	ASTM D-2047, NFSI & Euro-Norm R10



Shown on CatWalk

## CatWalk

is an opaque white material

## ClearWalk

is a transparent clear material



[sales@asphaltartusa.com](mailto:sales@asphaltartusa.com)  
[www.asphaltartusa.com](http://www.asphaltartusa.com)



Shown on CatWalk