



# Clear Window Perf

## 70/30 (1.5 mm hole)

### #WPERFC-UV-70

Clear Perforated Window Film (WPERFC-UV-70) offers first or second surface window graphics. 70/30 perforated film that allows graphics to be easily mounted to the inside or outside of windows, in a single step. Removable clear acrylic adhesive, with a universal double liner.

#### Features

- Removable clear acrylic adhesive
- Good UV Cure Printing
- Final tack is 5 hours
- One way-interior mount or Two Way
- Short to intermediate term applications (up to 2 years)

#### Applications

- Windows, Glass, Lexan and other clear flat surfaces

#### Printing White Ink Interior

##### Interior Mount One-Way Vision:

1. Reverse Print a full image
2. Spot print flood coat white
3. Spot print flood coat black

##### Two Way Perforated:

1. Reverse print a full image
2. Spot print flood coat white
3. right reading print full imaged

#### Printer Compatibility

Eco-Solvent, Latex, UVC and UV Gel (contact us for details)

#### Handling and Installation

Perforated material is vulnerable to tunneling due to less surface adherence to the liner. Always handle product with care, do not compromise the natural curl.

Clean application surface. In some applications material can be installed dry. Otherwise, use a small amount of application fluid. Be sure to leave a small gap between graphic and window gasket/frame. Always, finish with extra care to adhere around the edge of your graphic. In some cases, a 1/4" clear tape around the edges may be needed to prevent edge lifting.



#### Specifications:

Holes	1.5 mm
Media Type	Vinyl PVC
Sizes	54" X 98.4'
Perforation	70/30
Thickness	6.3 mil

Storage Conditions	Store in closed original packaging in a cool dry environment, 50°-77°F, Relative Humidity 50% RH. Shelf life up to 1 yr.
Printing Conditions	Temperature: 59°-86°F/ Humidity 30%-60% Recommend pre and post heater settings around 86°F



Baltimore, MD  
Charlotte, NC

[www.digitalcolorink.com](http://www.digitalcolorink.com)

877-616-8600

