

# FloorTac™

## Textures

ONE PART FLOOR GRAPHIC SOLUTION

FloorTac™ Textures is designed for vivid floor graphics that instantly take floors from drab to fab. Its removable, non-damaging adhesive makes FloorTac™ Textures ideal for short-term indoor advertising where graphics are applied to the floor. It is slip-rated and fire rated, making it ideal for public environments where safety is a top priority.

### CAN BE APPLIED TO:

- SHORT PILE CARPETS
- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE, OR TERRAZZO

**6.0** mil  
Textured White  
Polymeric  
PVC

■  
Matte



(Eco)Solvent  
Latex  
UV



Removable  
Gray Acrylic  
(Pressure Sensitive)



Widths up to 54 in



MONTHS DURABILITY  
UP TO  
**6**  
INTERIOR\*



### APPLICATIONS

SCHOOLS

HOSPITALS

RETAIL ADVERTISING

SUPERMARKETS

RESTAURANTS



**DRYTAC**<sup>®</sup>  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

## Textures

## TECHNICAL SPECIFICATION

FloorTac™ Textures is a 6 mil (150µ) printable, matte white phthalate-free polymeric PVC film with a removable, pressure sensitive gray acrylic adhesive protected by a poly coated Kraft release liner. The textured emboss on the film provides slip resistance.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- FIRE & SLIP RATED SINGLE PART FLOOR GRAPHIC SOLUTION
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

\* Up to 6 months indoor durability dependent upon floor-traffic and correct installation.

### INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

### PRODUCT STRUCTURE

|                      |   |
|----------------------|---|
| <b>Film</b>          | Textured Matte White Polymeric PVC          |
| <b>Adhesive</b>      | Removable Gray Acrylic (Pressure Sensitive) |
| <b>Release Liner</b> | 90# Poly Coated Kraft                       |

### PRODUCT CHARACTERISTIC

|                                  |  |                   |
|----------------------------------|--|-------------------|
| <b>Film Thickness</b>            | 6.0 mil (150µ)   | 7.4 mil<br>(185µ) |
| <b>Adhesive Layer</b>            | 1.4 mil (35µ)  |                   |
| <b>Fire Ratings</b>              | Class 1 or A (ASTM E-84) PASS (CAN/ULC-S102)   |                   |
| <b>Slip Ratings</b>              | Moderate Slip Potential (EN 13036-4) Passed (ANSI A137.1/ A326.3)<br>Dry: 58 Wet: 29 (AS HB198:2014 (AS/AZS 4586)) |                   |
| <b>Application Temperature</b>   | >-4°F (-20°C)  |                   |
| <b>Service Temperature Range</b> | -22°F to 302°F (-30°C to 150°C)  |                   |
| <b>Shelf Life</b>                | 2 years  |                   |
| <b>Storage Conditions</b>        | 59°F to 72°F (15°C to 22°C);<br>50 - 55% Relative Humidity   |                   |

### PRINTING RECOMMENDATIONS

UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.

# DRYTAC®

ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013