

BUBBLE-FREE PRO



BUBBLE-FREE APPLICATOR

Operators can mount and laminate digital prints and apply application tape to any flat surface, banner, table, flat furniture. Thickness of media up to 2-3/8", 5" optional.

- Quick mounting without any bubbles, wrinkles or creases
- Controlled application pressure prevents media stretching
- Easy positioning of material to be mounted
- Fast production speed for increased productivity
- Quick and easy to learn
- Self healing cutting mat



The pressure roller has 5/8" thick soft rubber coating to guarantee the bubble free & crease free application. The pressure roller is controllable from both sides. The pressure of the roller can be adjusted within a wide range by the pneumatic controllers. The castors with brakes allow the table to be easily moved or fixed in position.



Specifications:

- Working width: 65 in
- Working length: 8, 10, 12, or 16-1/2-ft
- Operation height: 33 in
- Max thickness of media: 2-1/4"
- Diameter of rubber roller: 4-1/4"
- 5mm safety PVC cutting mat - Included
- Side Tray – Included

Optional accessories:

- Silent Compressor (3cfm, 49-56 dB)
- Extra roller for large tables
- KeenCut EVO2 cutting unit
- Maximum thickness of media 5"



www.digitalcolorink.com
 877-616-8600
 Baltimore, MD | Charlotte, NC