

FloorTac™

Emerytex® White RB

ONE PART FLOOR GRAPHIC SOLUTION

FloorTac™ Emerytex® White RB is designed for one step, slip-rated floor graphics. Its removable, non-damaging adhesive makes FloorTac™ Emerytex® White RB ideal for short-term indoor advertising where graphics are applied to the floor. It is ideal for public environments where safety is a top priority.

CAN BE APPLIED TO:

- SHORT PILE CARPETS
- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE, OR TERRAZZO

Part Number: PFTE

8.0
mil

Textured White
Monomeric
PVC

Matte



(Eco) Solvent**
Latex
UV



Removable
Gray Acrylic
(Pressure Sensitive)



Widths up to 54 in



MONTHS DURABILITY
UP TO
9
INTERIOR*



APPLICATIONS

- SCHOOLS
- HOSPITALS
- RETAIL ADVERTISING
- SUPERMARKETS
- RESTAURANTS



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

FloorTac™

Emerytex® White RB

FloorTac™ Emerytex® White RB is a 8 mil (200µ) monomeric soft calendared white PVC film with a matte pebble textured finish, coated on one side with a pressure sensitive removable acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side. The textured emboss on the film provides slip resistance.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- SLIP & FIRE RATED SINGLE PART FLOOR GRAPHIC SOLUTION
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

* Up to 9 months indoor durability dependent upon floor-traffic and correct installation.

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film Matte White Pebble Textured Monomeric Soft Calendared PVC

Adhesive Removable Gray Acrylic (Pressure Sensitive)

Release Liner 2 Side PE Coated, 1 Side Siliconised Kraft

PRODUCT CHARACTERISTICS

Film Thickness 8 mil (200µ) | 9.4 mil

Adhesive Layer 1.4 mil (35µ) | (235µ)

Fire Rating Class 1 or Class A (ASTM E84)

Slip Certifications Moderate Slip Potential (HB198:2014 (AS/NZS 4586)) PASS (ANSI B101.3) *interior dry areas that are contaminant free*

Application Temperature >-4°F (-20°C)

Service Temperature Range -58°F to 212°F (-50°C to 100°C)

Shelf Life 1 year

Storage Conditions 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

**PRINTING RECOMMENDATIONS

UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.



www.digitalcolorink.com
877-616-8600

Baltimore, MD | Charlotte, NC

DRYTAC®

ADHESIVE SCIENCE

www.drytac.com