

# Dynamic Plus

## Gloss

Dynamic Plus Gloss is a 3.2 mil (80μ) monomeric soft calendared PVC laminating film with a glossy finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a Kraft release paper that is PE-coated on one side and siliconized on the release side.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE ON FLEXIBLE MEDIA SUBSTRATES WHERE A GLOSS FINISH IS REQUIRED
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, AND EVENT SIGNAGE

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

Film	Gloss Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	1 Side PE Coated, 1 Side Siliconized Kraft

### PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80μ)   4.2 mil
Adhesive Layer	1 mil (25μ)   (105μ)
Film/Adhesive Ratio	3.2:1
UV Protection	Yes
Outdoor Durability	2 Years
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended



[www.digitalcolorink.com](http://www.digitalcolorink.com) 877-616-8600  
Baltimore, MD | Charlotte, NC

**DRYTAC**<sup>®</sup>  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# Dynamic Plus

## Lustre

Dynamic Plus Lustre is a 3.2 mil (80µ) monomeric soft calendared PVC laminating film with a lustre finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a Kraft release paper that is PE-coated on one side and siliconized on the release side.

- LOW SHEEN WITHOUT LOSS OF CONTRAST OR SHARPNESS MAKES DYNAMIC PLUS LUSTRE EFFECTIVE FOR A WIDE RANGE OF APPLICATIONS

● IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS AND EVENT SIGNAGE.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

Film	Lustre Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	1 Side PE Coated, 1 Side Siliconized Kraft

### PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ)   4.2 mil
Adhesive Layer	1 mil (25µ)   (105µ)
Film/Adhesive Ratio	3.2:1
UV Protection	Yes
Outdoor Durability	2 Years
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended



[www.digitalcolorink.com](http://www.digitalcolorink.com) 877-616-8600  
Baltimore, MD | Charlotte, NC

**DRYTAC**<sup>®</sup>  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# Dynamic Plus

## Matte

Dynamic Plus Matte is a 3.2 mil (80 $\mu$ ) monomeric soft calendared PVC laminating film with a matte finish coated on one side with a pressure sensitive acrylic adhesive that is protected by a Kraft release paper that is PE-coated on one side and siliconized on the release side.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE WHERE A NON-GLARE FINISH IS REQUIRED OR WHERE SPECIFIC LIGHTING CONDITIONS CANNOT BE CONTROLLED
- IDEAL FOR POP DISPLAYS, EXHIBITION GRAPHICS AND PROMOTIONAL SIGNAGE THAT WILL BE VIEWED UNDER DIRECT

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

Film	Matte Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	1 Side PE Coated, 1 Side Siliconized Kraft

### PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80 $\mu$ )   4.2 mil
Adhesive Layer	1 mil (25 $\mu$ )   (105 $\mu$ )
Film/Adhesive Ratio	3.2:1
UV Protection	Yes
Outdoor Durability	2 Years
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended



[www.digitalcolorink.com](http://www.digitalcolorink.com) 877-616-8600  
Baltimore, MD | Charlotte, NC

**DRYTAC**<sup>®</sup>  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)