

# FloorTac™

## with Dynamic™ Plus Sand

FloorTac™ is a 3.2 mil (80µ) printable matte white polymeric PVC film with a removable, pressure sensitive gray acrylic adhesive protected by a poly coated Kraft release liner.

Dynamic Plus Sand is a 3.2 mil (80µ) monomeric soft calendared PVC laminating film with a matte sand finish coated on one side with a pressure sensitive acrylic adhesive that is protected by a Kraft release paper that is PE-coated on one side and siliconized on the release side.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- THE PAIRED SOLUTIONS CARRIES SEVERAL SLIP RATINGS & CERTIFICATIONS
- UP TO 6 MONTHS\* DURABILITY INDOORS

### FloorTac™



(Eco) Solvent  
Latex  
UV

\* Up to 6 months indoor durability dependent upon floor-traffic and correct installation.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### FloorTac™

#### PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	Removable Gray Acrylic (Pressure Sensitive)
Release Liner	90# Poly Coated Kraft

### FloorTac™

#### PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ)   4.2 mil
Adhesive Layer	1 mil (25µ)   (105µ)
Fire Ratings	Class A or 0 (ASTM E-84) PASS (CAN/ULC-S102)
Application Temperature	>-4°F (-20°C)
Service Temperature Range	-22°F to 302°F (-30°C to 150°C)

### Dynamic™ Plus Sand

#### PRODUCT STRUCTURE

Film	Matte Sand Textured Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	1 Side PE Coated, 1 Side Siliconised Kraft

### Dynamic™ Plus Sand

#### PRODUCT CHARACTERISTICS

Film Thickness	3.2 mil (80µ)   4.2 mil
Adhesive Layer	1 mil (25µ)   (105µ)
UV Protection Factor	Film and adhesive contain UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Slip Rating	PASS (ANSI A137.1/A326.3) <i>interior dry areas that are contaminant free</i>
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)

Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity



Digital  
Color<sub>ink</sub>

www.digitalcolorink.com  
877-616-8600  
Baltimore, MD | Charlotte, NC

**DRYTAC**<sup>®</sup>  
ADHESIVE SCIENCE

www.drytac.com