

Envi Wallgraphics Media

High Performance Digital Wallcovering
Pre-pasted, PVC-Free, Strippable

Envi Wallgraphics offer a renewable fiber-based 10% PCW alternative to vinyl for walls, windows and other rigid surfaces in the home and in commercial settings/environments.

Envi Wallcovering meets the strict California 01350 standards for indoor air quality - a prerequisite for LEED credit qualification, and carries a class "A" fire rating based on ASTM E-84 standard testing for smoke generation and flame spread.

Specify Envi Wallgraphics when looking to boldly enhance a small space or an entire establishment in an environmentally conscious way.

For paper samples, visit www.mpm.com or call 877-877-2098.

Appropriate on-product FSC logo:



Typical Properties	UOM	C2896-108	C2896-148
Basis Weight (24 x 36/500)	lb./3,000f ²	104	140
Basis Weight GSM	g/m ²	166	228
Caliper	mils / mm	6.7 / 0.17	9.6 / 0.24
Dry Tensile CD	pli / kN/m	37 / 6.48	38 / 6.65
Dry Tensile MD	pli / kN/m	45 / 7.88	55 / 9.63
Elmendorf Tear CD	grams	130	200
Elmendorf Tear MD	grams	125	190
Sheffield Smoothness	Sheffield Units	15	18
Color	L/a/b	95.5/-0.3/2.8	95.5/-0.3/2.8
Parker Print Surf		1.3	1.4
Opacity	%	96	97.9
Gloss (75 degrees)	GU	15	13

This information is presented in good faith for verification and corroboration by the prospective user. No warranty is implied or to be assumed.

Features and Benefits

• Performance and Aesthetics

- Bright white for beautiful image reproduction
- Ultra-smooth print surface optimized for inkjet printing with UV and latex inks
- Quick dry print surface for convenience and enhanced productivity
- Matte finish to minimize glare
- Polymer reinforced for strength and durability
- Washable/scrubbable surface perfect for light to moderate traffic areas
- Meets California 01350 standards for indoor air quality
- Breathable to reduce mold and mildew
- Prepasted - requiring only water to activate the adhesive
- Class "A" rating for both smoke generation and flame spread by the ASTM E-84 standard
- Complies with REACH, Lacey Act, CPSIA and RohS requirements

• Made with the environment in mind

- The FSC logo ensures responsible use of forest resources certified by a third party
- Made with third-party Green-e® certified Wind Power Renewable Energy Certificates
- Manufactured Carbon Neutral with Verified Emission Reductions certified under the Climate Action Reserve Protocol
- Manufactured Process Chlorine Free
- Manufactured under an ISO 14001:2004 Certified Environmental Management System

Installation instructions and warranty are available at www.mpm.com/enviwallgraphics.