

Facemount®

Facemount® is a 1 mil (25µ) high quality, optically clear PET film, coated on both sides with a pressure sensitive, permanent solvent acrylic adhesive, both of which are protected by a clear PET release liner. Facemount® is made using the finest optical clarity components. It offers excellent UV stability to graphic prints.

- RECOMMENDED FOR SECOND SURFACE MOUNTING (COMMONLY REFERRED TO AS FACE MOUNTING) OF IMAGES TO CLEAR SUBSTRATES, SUCH AS PETG™, PLEXIGLAS™, ACRYLIC, POLYCARBONATE, AND GLASS.
- IDEAL FOR LENTICULAR IMAGING APPLICATIONS, BACKLIT DISPLAY TRANSPARENCIES, TOUCH SCREEN DISPLAYS, AND HIGH QUALITY PHOTOGRAPHIC AND INKJET PRINTED IMAGES
- SUITABLE FOR INDOOR AND SHORT-TERM OUTDOOR USE



www.digitalcolorink.com
877-616-8600
Baltimore, MD | Charlotte, NC

For more information,
performance and warranty guide
lines please contact your local
Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Release Liner	Siliconized 1 Side PET
Adhesive	Permanent Solvent Acrylic (Pressure Sensitive)
Film	Clear PET
Adhesive	Permanent Solvent Acrylic (Pressure Sensitive)
Release Liner	Siliconized 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	1 mil (25µ)	2.8 mil (71µ)
Adhesive Layer	0.9 mil (23µ)	
Film/Adhesive Ratio	0.9:1:0.9	
UV Protection Factor	UV Stable	
Outdoor Durability	2 years	
Peel Strength (20 min, FTM1)	12.8 N/25mm (glass 24 hours)	
Service Temperature Range	-40°F to 212°F (-40°C to 100°C)	
Shelf Life	1 year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTING

Roller Laminator

Temperature: Room Temperature to 104°F (40°C)
Speed: 1 ft to 8 ft (0.3m to 2.5m) per minute

Press

Not Recommended

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com