

Interlam™

Pro Emerytex®

Interlam™ Pro Emerytex® is a 4 mil monomeric soft calendared PVC laminating film with a matte pebble textured finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side. Interlam™ Pro Emerytex® has been tested according to the EN 13036-4 test method and awarded a rating of low slip potential.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN HIGH TRAFFIC INDOOR AND OUTDOOR DISPLAY AREAS
- PROVIDES UV PROTECTION FOR OUTDOOR GRAPHICS
- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE, FLOOR GRAPHICS, AND OTHER SIGNAGE WHERE A SCUFF-RESISTANT FINISH IS REQUIRED
- CAN BE COMBINED WITH DRYTAC'S FLOORTAC™ PRINT MEDIA TO CREATE A SLIP-RESISTANT FLOOR GRAPHIC FOR LOW TO MID-TRAFFIC AREAS (UP TO 6 MONTHS)

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Pebble Textured Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 1 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4 mil	5 mil
Adhesive Layer	1 mil	
Film/Adhesive Ratio	4:1	
UV Protection Factor	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image	
Outdoor Durability	3 Years	
Application Temperature	>41°F (20°C)	
Service Temperature Range	-13°F to 302°F (-25°C to 150°C)	
Peel Strength (20 min, FTM1)	11 N/25mm	
Shelf Life	1 year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®

ADHESIVE SCIENCE



www.digitalcolorink.com

877-616-8600

Baltimore, MD | Charlotte, NC

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA

customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com