

Pro Lustre

Interlam™ Pro Lustre is a 3 mil monomeric soft calendared PVC laminating film with a lustre finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side.

- LOW SHEEN WITHOUT LOSS OF CONTRAST OR SHARPNESS MAKES INTERLAM™ PRO LUSTRE EFFECTIVE FOR A WIDE RANGE OF APPLICATIONS
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, AND EVENT SIGNAGE

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

| | |
|----------------------|--|
| Film | Lustre Monomeric Soft Calendared PVC |
| Adhesive | Acrylic (Pressure Sensitive) |
| Release Liner | 2 Side PE Coated, 1 Side Siliconized Kraft |

PRODUCT CHARACTERISTIC

| | |
|-------------------------------------|--|
| Film Thickness | 3 mil (75µ) 4 mil |
| Adhesive Layer | 1 mil |
| Film/Adhesive Ratio | 3:1 |
| UV Protection Factor | Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image |
| Outdoor Durability | 3 Years |
| Application Temperature | >41°F (20°C) |
| Service Temperature Range | -13°F to 302°F (-25°C to 150°C) |
| Peel Strength (20 min, FTM1) | 11 N/25mm |
| Shelf Life | 1 year |
| Storage Conditions | 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity |

PROCESS SETTINGS

| Equipment Type & Temperature | Speed |
|---|--|
| Roller Laminator Room temperature to 104°F (40°C) | 1 ft to 8 ft (0.3m to 2.5m) per minute |
| Press | Not recommended |

DRYTAC®

ADHESIVE SCIENCE



www.digitalcolorink.com
877-616-8600
Baltimore, MD | Charlotte, NC

USA
5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013