

# Polar®

## Blockout

Polar® Blockout is an opaque printable block out film ideal for two-sided window graphics and other block out layer needs. To create eye-catching two-sided window graphics, simply combine Polar® Blockout with a reverse printed clear print media, such as Drytac SpotOn® Clear Gloss or Polar® Dynamic Clear. Polar® Blockout's high opacity prevents graphics from showing through on the other side when using as a cover up graphic or label.

- CREATE DOUBLE-SIDED WINDOW GRAPHICS WITHOUT THE NEED FOR INK LAYERS OR WHITE INK.
- IDEAL FOR APPLICATIONS WHERE PREVENTING GRAPHIC SHOW-THROUGH ON OTHER SIDE IS NEEDED.

**5.9**  
mil

Opaque  
White Polymeric  
PVC



Matte



(Eco) Solvent  
Latex  
UV



Permanent Acrylic  
Pressure-Sensitive  
Adhesive



Widths up to 54 in



**INTERIOR & EXTERIOR**  
(with matching overlamine)

CREATE EASY TWO-WAY WINDOW GRAPHICS



### APPLICATIONS

- Two-Sided Window Graphics
- Smooth Glass Surfaces
- Point Of Sale Graphics
- Decals & Stickers



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

## Blockout

Polar® Blockout is a proprietary 5.9 mil (149.86µ) highly opaque layered white polymeric film with a matte finish. It is coated with a pressure-sensitive, permanent aqueous acrylic adhesive which is protected by a 78# PE coated, release paper. Polar® Blockout is designed for use as two-way window graphics, cover-up labels and decals that require high opacity stock.

### INSTALLATION

#### RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

Film	Opaque Matte White Film
Adhesive	Permanent Acrylic Pressure-Sensitive
Release Liner	78# Clay Coated

### PRODUCT CHARACTERISTICS

Film Thickness	5.9 mil (149.86µ)   7.1 mil (180.34µ)
Adhesive Layer	1.2 mil (30.48µ)   (180.34µ)
Outdoor Durability	7 Years (ink dependent and with matching overlaminate)
Application Temperature	-4°F (-20°C)
Service Temperature Range	-49°F to 230°F (-45°C to 110°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### OVERLAMINATE RECOMMENDATIONS

When using Polar® Blockout, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Blockout are Drytac's Weathershield® overlaminates.



[www.digitalcolorink.com](http://www.digitalcolorink.com)  
877-616-8600

Baltimore, MD | Charlotte, NC

# DRYTAC®

## ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013