

# Polar®

## Polymeric

The high opacity of Polar® Polymeric provides an excellent printing surface and offers a consistent white point. Polar® Monomeric also offers excellent indoor and outdoor durability with a 3+ year lifespan for exterior applications. With both permanent and removable adhesive options, Polar® Polymeric maximizes adhesive performance on a wide variety of substrates.

- PHTHALATE-FREE PRODUCTS
- PERMANENT OR REMOVABLE OPTIONS
- EXCELLENT WHITE POINT FOR PRINTING

**3.2**  
mil

White  
Polymeric  
PVC

Matte or  
Gloss



(Eco) Solvent  
Latex  
UV



Gray or Clear  
Removable or Permanent  
Acrylic (Pressure Sensitive)



Widths up to 54 in



EXTERIOR & INTERIOR

**CONSISTANT PRINTING SURFACE**



## APPLICATIONS

POP AND ADVERTISING GRAPHICS  
POSTERS  
EXHIBITION GRAPHICS  
GENERAL SIGNAGE  
CONSTRUCTION BARRICADES



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)



# Polar®

## Polymeric

Polar® Polymeric is a 3.2 mil white monomeric PVC film with either a gloss or matte finish. Polar® Polymeric is either coated with a gray permanent or removable, pressure sensitive solvent acrylic adhesive or a clear removable, pressure sensitive acrylic adhesive that is protected by either a 78# Poly Coated Kraft release liner (or a 90# release liner for the Polar® Poly P90).

### PERMANENT ADHESIVE OPTIONS

- **Polar Poly Gloss P:** Gloss Finish with Gray Permanent Adhesive
- **Polar Poly Matte P:** Matte Finish with Gray Permanent Adhesive
- **Polar Poly Gloss P90:** Gloss Finish with Gray Permanent Adhesive (90# release liner)
- **Polar Poly Matte P90:** Matte Finish with Gray Permanent Adhesive (90# release liner)

### REMOVABLE ADHESIVE OPTIONS

- **Polar Poly Gloss R:** Gloss Finish with Gray Removable Adhesive
- **Polar Poly Matte R:** Matte Finish with Gray Removable Adhesive
- **Polar Poly Gloss RC:** Gloss Finish with Clear Removable Adhesive
- **Polar Poly Matte RC:** Matte Finish with Clear Removable Adhesive

### INSTALLATION

#### RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

Film	Gloss White Polymeric PVC	Matte White Polymeric PVC
Adhesive	Gray or Clear Removable Solvent Acrylic (Pressure Sensitive) or Gray Permanent Solvent Acrylic (Pressure Sensitive)	Gray or Clear Removable Solvent Acrylic (Pressure Sensitive) or Gray Permanent Solvent Acrylic (Pressure Sensitive)
Release Liner	78# Poly Coated Kraft (Polar Poly P90 has 90# Poly Coated Kraft)	

### PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil   4.2 mil
Adhesive Layer	1 mil
Film/Adhesive Ratio	3:2:1
UV Protection Factor	Not Applicable
Outdoor Durability	3 Years
Application Temperature	>21°F (-6°C)*
Service Temperature Range	-22°F to 176°F (-30°C to 80°C)*
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

\*Polar Poly Matte/Gloss R has an application temperature of >4°F (-20°C) and a service temperature range of -22°F to 302°F (-30°C to 150°C)

### OVERLAMINATE RECOMMENDATIONS

When using Polar® Polymeric, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Polymeric are Drytac's WipeErase® and Interlam™ Pro overlaminates.



www.digitalcolorink.com  
877-616-8600  
Baltimore, MD | Charlotte, NC

**DRYTAC®**  
ADHESIVE SCIENCE

### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
customerservice@drytac.com  
Tel: +1 800.280.6013

www.drytac.com