

Polar®

Transit

Polar® Transit can be adhered to smooth, flat surfaces such as hockey rinks and bus king, queen and tail posters. Its rugged qualities make Polar® Transit ideal for outdoor transit applications such as temporary fleet graphics and transportation signage.

- IDEAL FOR OUTDOOR TRANSIT APPLICATIONS
- TEMPORARY FLEET GRAPHICS AND TRANSPORTATION SIGNAGE
- CAN BE USED FOR ARENA ADVERTISING

3.2
mil

White
Polymeric
PVC



Matte



(Eco) Solvent
Latex
UV



Grey Removable
Acrylic
(Pressure Sensitive)



Widths up to 62 in



EXTERIOR & INTERIOR
(6 Months Removability)

IDEAL FOR OUTDOOR TRANSIT APPLICATIONS



APPLICATIONS

TRANSIT ADVERTISING

ARENA ADVERTISING

GENERAL SIGNAGE



Certified for
HP Latex Inks



DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

Transit

Polar® Transit is a 3.2 mil (80µ) premium, matte white polymeric self-adhesive PVC film with a high quality, removable grey acrylic adhesive that is protected by a 90# PE Coated Kraft release liner. Polar® Transit allows for adhesion to smooth, flat surfaces such as hockey rinks and bus king, queen and tail posters.

- IDEAL FOR OUTDOOR TRANSIT APPLICATIONS
- TEMPORARY FLEET GRAPHICS AND TRANSPORTATION SIGNAGE
- CAN BE USED FOR ARENA ADVERTISING

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

04092020

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	Grey Removable Acrylic (Pressure Sensitive)
Release Liner	90# PE Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ) 4.2 mil (105µ)
Adhesive Layer	1 mil (25µ) (105µ)
Film/Adhesive Ratio	3:2.1
Outdoor Durability	5 Years (6 Months Removability)
Fire Ratings	Class A or Class 0 (ASTM E-84) PASS (CAN/ULC-S102)
Application Temperature	-5°F (-20°C)
Service Temperature Range	-40°F to 212°F (-40°C to 100°C)
Peel Strength (24 Hour Test)	12 ozf/in
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar® Transit, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Transit are Drytac's Interlam™ Pro overlaminates.

DRYTAC®
ADHESIVE SCIENCE



www.digitalcolorink.com
Office: 301-937-8772
Toll: 877-616-8600

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013