

# ReTac<sup>®</sup>

## Smooth 150

Our 6 mil, white polymeric printable PVC film with ReTac<sup>®</sup> ultra removable adhesive technology is designed for graphics that need to be easily installed, removed and re-positioned.


Dimensionally stable, ReTac<sup>®</sup> Smooth 150 can be applied and re-positioned multiple times without stretching or tearing. And, with ReTac<sup>®</sup> on the back, you never have to worry about adhesive setting up, being left behind, or damaging the surface it is adhered to when graphics are removed.

ReTac<sup>®</sup> Smooth 150 has a Class 0 Fire Rating for surface spread of flame.

- IDEAL FOR INTERIOR WALL GRAPHIC APPLICATIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

**6** mil White Phthalate-Free Polymeric PVC  Matte

 (Eco) Solvent Latex UV

 ReTac<sup>®</sup> ultra removable and re-positionable adhesive

 Widths up to 54 in

 **5** YEARS DURABILITY **INTERIOR AND EXTERIOR**  
(2 YEAR REMOVABILITY EXTERIOR)

### EASY APPLICATION AND REMOVAL



### APPLICATIONS

- Smooth Flat Surfaces
- Point Of Sale Graphics
- Interior Décor
- Decals & Stickers



Certified for  
HP Latex Inks

**DRYTAC<sup>®</sup>**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# ReTac®

## Smooth 150

ReTac® Smooth 150 is a 6 mil printable white, phthalate-free polymeric PVC film, coated on one side with ReTac® ultra removable adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. ReTac® Smooth 150 can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- RETAC® IS A PHTHALATE-FREE FILM.
- IDEAL FOR REMOVABLE WALL DECALS, APPLIQUES AND WALL MURALS.
- SUITABLE FOR USE ON MOST INDOOR SURFACES, PAINTED WALLS, MELAMINE, GLASS, AND LOW SURFACE ENERGY SUBSTRATES.
- RETAC® SMOOTH 150 HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Matte White Polymeric PVC
<b>Adhesive</b>	ReTac® ultra removable and re-positionable adhesive technology
<b>Release Liner</b>	135 gsm 1 side siliconized clay coated Kraft paper

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	6 mil	6.9 mil
<b>Adhesive Layer</b>	0.9 mil	
<b>Film/Adhesive Ratio</b>	6:0.9	
<b>UV Protection Factor</b>	Not Applicable	
<b>Outdoor Durability</b>	5 year; 2 years removability	
<b>Application Temperature</b>	>41°F (5°C)	
<b>Service Temperature Range</b>	-4°F to 149°F (-20°C to 65°C)	
<b>Flame Retardancy</b>	Class 0 BS 476 - Part 6 & 7 Fire Rating	
<b>Shelf Life</b>	2 years	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### OVERLAMINATE RECOMMENDATIONS

When using ReTac® Smooth 150, an overlaminate can be used for maximum life expectancy. Products recommended for use with ReTac® Smooth 150 are Drytac's Interlam™ Pro overlaminates.



[www.digitalcolorink.com](http://www.digitalcolorink.com)  
877-616-8600  
Baltimore, MD | Charlotte, NC

**DRYTAC®**  
ADHESIVE SCIENCE

**USA**  
5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)