

ReTac®

Textures **WOODGRAIN**

ADDS VISUAL INTEREST TO ANY PRINT

ReTac® Textures Woodgrain can add depth and visual appeal to static, flat images with its embossed woodgrain finish. With ReTac® on the back, eye-catching graphics printed on ReTac® Textures Woodgrain can easily be removed and repositioned multiple times without the worry of adhesive residue being left behind. This phthalate-free film can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- IDEAL FOR INTERIOR PROMOTIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

150
micron

White
Phthalate-Free
Polymeric
PVC



Matte



(Eco)Solvent
Latex
UV



ReTac® ultra removable
and re-positionable
adhesive



Widths up to 54 in



INTERIOR AND EXTERIOR
(2 YEAR REMOVABILITY EXTERIOR)



APPLICATIONS

Smooth Flat Surfaces
Point Of Sale Graphics
Interior Décor
Decals & Stickers



COLORCAPTURE
CREATE YOUR OWN WALLCOVERINGS

DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

ReTac®

Textures **WOODGRAIN**

ReTac® Textures Woodgrain is a 150µ (6 mil) printable, matte white phthalate-free polymeric PVC film with ReTac® ultra removable adhesive. It has an embossed woodgrain like finish that adds depth and visual appeal to static, flat graphics. A subtle texture like woodgrain draws attention to your image or message in a distinct and creative way.

● RETAC® TEXTURES IS A PHTHALATE-FREE FILM.

● IDEAL FOR WALL GRAPHICS, CUSTOM WALL MURALS, INTERIOR DÉCOR, RETAIL DISPLAYS, TRADE SHOW GRAPHICS AND SIGNAGE, AND TEXTURED LABELS.

INSTALLATION

RECOMMENDATION

Please see Wall Graphic

Installation & Removal Instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information,
performance and warranty guide
lines please contact your local
Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White PVC
Adhesive	ReTac® ultra removable and re-positionable adhesive technology
Release Liner	143 gsm 2 Side PE Coated, 1 Side Solventless Siliconised Fine Paper

PRODUCT CHARACTERISTIC

Film Thickness	6 mil (150µ)	7 mil (175µ)
Adhesive Layer	1 mil (25µ)	
Film/Adhesive Ratio	6:1	
UV Protection Factor	Not Applicable	
Outdoor Durability	5 year; 2 years removability	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	



www.digitalcolorink.com
877-616-8600
Baltimore, MD | Charlotte, NC

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com