


# SpotOn®

## EASY BUBBLE FREE APPLICATION

SpotOn® has a unique dot pattern removable adhesive that is virtually undetectable, but allows graphics to be installed with minimal effort, remain in place for the duration of the application, and removed with ease. The film's adhesive allows for easy, bubble-free application of vibrant graphics to a wide range of substrates without the need for tools or wet installation. Available in clear matte, clear gloss, white matte and white gloss finishes. SpotOn® is commonly used for window graphics but can also be used for short-term indoor applications such as wall graphics, tradeshow graphics or retail graphics that require seasonal change out.

- IDEAL FOR INDOOR OR SHORT-TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

**4** mil Clear or White Monomeric PVC   Matte or Gloss



 Widths up to 54 in

**3** YEARS DURABILITY INTERIOR **6** MONTHS DURABILITY EXTERIOR

## LIMITED QUANTITIES

...a quarendum ut. Veri paulo an sea, ei vix propri...  
...t vocent mediocritatem, pro ex elitr iudicabit scrip...  
...egat his an. Ad ius regione mentitum apeirian, id elig...  
...oni eu. Vim timeam imperdiet temporibus at. Eiu...

### APPLICATIONS

General Signage

Retail Promotions

Window Graphics

Certified for  
HP Latex Inks



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

SpotOn® is a 4 mil printable monomeric PVC film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy, bubble-free application of vibrant graphics to a wide range of substrates. SpotOn® is available in clear matte, clear gloss, white matte and white gloss finishes.

- IDEAL FOR INDOOR AND SHORT-TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

### INSTALLATION

#### RECOMMENDATION

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

### PRODUCT STRUCTURE

#### Film

Clear Matte, Clear Gloss, White Matte or White Gloss Monomeric PVC

#### Adhesive


Dot Pattern Removable Polyacrylate

#### Release Liner

135 gsm Siliconised 1 Side Bleached Clay Coated Kraft

### PRODUCT CHARACTERISTIC

#### Film Thickness

4 mil 

#### Adhesive Layer

0.5 mil

#### Film/Adhesive Ratio

4:0.5

#### UV Protection Factor

Not Applicable

#### Outdoor Durability

Short-Term

#### Application Temperature

>41°F (5°C)

#### Service Temperature Range

-4°F to 149°F  
(-20°C to 65°C)

#### Flame Retardancy

B1  
(According to DIN 4102-1)

#### Shelf Life

1 year

#### Storage Conditions

64°F to 77°F (18°C to 25°C);  
40 - 65% Relative Humidity

# DRYTAC®

## ADHESIVE SCIENCE



[www.digitalcolorink.com](http://www.digitalcolorink.com)

877-616-8600

Baltimore, MD | Charlotte, NC

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA

[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013