

FloorTac™

Floor Graphic Material

FloorTac™ is designed for attention-grabbing floor graphics that instantly take floors from drab to fab. Its removable, non-damaging adhesive makes FloorTac™ ideal for short-term indoor advertising where graphics are applied to the floor. When combined with Drytac's Emerytex® laminating films, FloorTac™ provides a certified slip-resistant finish for the ultimate floor graphic solution.

CAN BE APPLIED TO:

- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE, OR TERRAZZO

3.2 mil
White Polymeric PVC

Matte



(Eco)Solvent
Latex
UV



Removable
Gray Acrylic
(Pressure Sensitive)



Widths up to 54 in



3 MONTHS DURABILITY
INTERIOR

ENGINEERED WITH NO-LIFT TECHNOLOGY



APPLICATIONS

SCHOOLS
HOSPITALS
RETAIL ADVERTISING
SUPERMARKETS
RESTAURANTS



DRYTAC
ADHESIVE SCIENCE

www.drytac.com

FloorTac™

Floor Graphic Material

FloorTac™ is a 3.2 mil printable matte white polymeric PVC film with a removable, pressure sensitive gray acrylic adhesive protected by a polycoated Kraft release liner. It is recommended for use with Drytac's Emerytex® laminating films to provide slip resistance.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- SUITABLE FOR MID TO HEAVY FOOT TRAFFIC AREAS
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

OVERLAMINATE RECOMMENDATIONS
When using FloorTac™, an overlamine can be used for maximum life expectancy. Products recommended for use with FloorTac™ are Drytac's Emerytex® overlaminates.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	Removable Gray Acrylic (Pressure Sensitive)
Release Liner	90# Poly Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ)	4.2 mil
Adhesive Layer	1 mil	
Film/Adhesive Ratio	3.2:1	
UV Protection Factor	Not Applicable (unless combined with Emerytex®)	
Outdoor Durability	Not Applicable	
Application Temperature	>-4°F (-20°C)	
Service Temperature Range	-22°F to 302°F (-30°C to 150°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

DRYTAC®
ADHESIVE SCIENCE



www.digitalcolorink.com
877-616-8600
Baltimore, MD | Charlotte, NC

USA
5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com

Interlam™

Pro Emerytex®

Interlam™ Pro Emerytex® is a 4 mil monomeric soft calendared PVC laminating film with a matte pebble textured finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side. Interlam™ Pro Emerytex® has been tested according to the EN 13036-4 test method and awarded a rating of low slip potential.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN HIGH TRAFFIC INDOOR AND OUTDOOR DISPLAY AREAS
- PROVIDES UV PROTECTION FOR OUTDOOR GRAPHICS
- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE, FLOOR GRAPHICS, AND OTHER SIGNAGE WHERE A SCUFF-RESISTANT FINISH IS REQUIRED
- CAN BE COMBINED WITH DRYTAC'S FLOORTAC™ PRINT MEDIA TO CREATE A SLIP-RESISTANT FLOOR GRAPHIC FOR LOW TO MID-TRAFFIC AREAS (UP TO 6 MONTHS)

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Pebble Textured Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 1 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4 mil 5 mil
Adhesive Layer	1 mil
Film/Adhesive Ratio	4:1
UV Protection Factor	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	3 Years
Application Temperature	>41°F (20°C)
Service Temperature Range	-13°F to 302°F (-25°C to 150°C)
Peel Strength (20 min, FTM1)	11 N/25mm
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®

ADHESIVE SCIENCE



www.digitalcolorink.com
Office: 301-937-8772
Toll: 877-616-8600

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com