

PERFORMANCE GUIDE

High Strength Rubber Transfer Adhesive

GS Series Tapes


Version: 2 Date: 4/2019 Approved by: JNP

Product Description

The GS Series high-strength rubber transfer adhesive consists of an unsupported proprietary rubber-based pressure-sensitive formulation and a 60# C2S White SCK release liner. GS-Series tape has very aggressive tack and peel properties combined with exceptional shear strength.

Product Construction

- Carrier: NA
- Adhesive: GS High Strength Rubber
- Liner: 60# White SCK



Features

- Available in 5.0 mil to 50mil Thicknesses
- Available in 0.5" to 11.5" adhesive widths
- MTO sizes will ship in 10 15 working days
- All rolls are manufactured with ungummed edges.

<u>Benefits</u>

- High initial tack and adhesion
- Excellent adhesion to a wide variety of substrates including LSE plastics
- Excellent as a gap filler or moisture barrier
- Durable enough to replace mechanical fasteners

Applications

- General purpose mounting & bonding applications
- Flooring installation
- Recreational Vehicle
- Product Assembly
- POP, Signage & Graphics
- Appliance
- Gaskets
- Packaging



www.digitalcolorink.com 877-616-8600 Baltimore, MD | Charlotte, NC

GS Series Physical Properties			
Thickness	Mils		
Adhesive	5.0 - 50.0		
Liner	3.5		
Total Thickness	8.5 – 53.5		
Performance Test	Test Method	Typical Values	
Loop tack	PSTC-16-Method A	Lbs./in.	Oz/in.
Stainless Steel	Backed with 2 mil PET	20.0 +	80
Peel Adhesion	PSTC-101-Method A	Lbs./in.	Oz/in.
2 mil PET Backed			,
30 minute dwell	Stainless Steel	22.0+	136
Shear	PSTC-107-Method A	Hours to Fail	
	72°F	300+	
1 kg weight	/2 F	300+	

Values given are typical and not for use in specifications

SERVICE TEMPERATURE

Application:Above 50°F (10°C) for best performanceEnd Use:-40°F to 180°F (-40°C to 82.2°C)

APPLICATION DETAILS

For best performance surfaces must be clean, dry and free of any oil, grease or other contaminant.

SHELF LIFE

Two-year shelf life when stored at 75°F. (24°C.) and 50% relative humidity or less. It is recommended that the product be stored in its original package until ready to use.

CALL 1-800-328-2619 for additional product information

IMPORTANT NOTICE: The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the foregoing provisions unless in a specific agreement signed by the officers of seller and manufacturer. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

[™] Trademark of Morgan Adhesives Company LLC [®] Registered Trademark of Morgan Adhesives Company LLC

www.Mactac.com



