

www.Mactac.com

Version #7 (0218)
Approved by J. S.

Product

PermaPrint® IP5000

Permacolor®

The **Permacolor** system is a series of pressure sensitive products for mounting and overlaminating in the imaging industries. Pressure sensitive **Permacolor** provides fast, efficient processing through cold roll lamination techniques without the need for heat, drying or messy coating operations.

Product Description

The **PermaPrint® mounting films** consist of acrylic mounting adhesives with and without film carriers. These smooth, adhesive constructions permit distortion-free mounting of photographic prints and other graphic images to a wide variety of substrates including Fome-Cor®, Gatorfoam®, Crescent® board, Masonite® and Sintra®.

IP5000 consists of a thin, opaque plastic film coated on both sides with an acrylic pressure sensitive adhesive. A moisture stable, polycoated kraft liner protects the adhesive.

IP5000 was designed for quick adhesion to a variety of mounting surfaces and can be used in both indoor and outdoor applications. The single release liner permits easy lamination and eliminates the need to remove a second liner in applications where that may be difficult or impossible.

Physical Properties

Property	Typical Values	Test Method
Thickness mils (mm) Adhesive Carrier and Adhesive	1/1 (0.028/0.028) 4.5 (0.114)	ASTM D-645
Peel Adhesion, lb. /in. (N/25mm) Stainless Steel - 30 min. - 24 hr.	3.5 (19) 4.0 (22)	PSTC - 3
Quick Tack, lb. /in² (N/25mm) Stainless Steel	4.4 (17.5)	MACtac CTM-25
Shear, Hours to Fail Stainless Steel	150	PSTC - 7
Temperature Ranges Application for best results: End Use:	50° to 120°F (10° - 49°C) -20° to 200°F (-30° to 93°C)	
Adhesive pH	Neutral	TAPPI-529

Shelf Life

Two years when stored at 75°F (24°C) and 50% relative humidity or less. Note: Mactac recommends that rolls be stored on end or suspended from the core.

Limitations

- 1) The user is responsible for determining the product's suitability, including adhesion and if needed, removal characteristics when used in applications other than listed specifically in this Performance Guide.
- 2) If there are any questions about applications, please contact your Mactac sales representative to discuss your requirements for recommendations.
- 3) If this is a printed Performance Guide it is an uncontrolled document. Please check the Mactac website for the latest, most up-to-date version.

General Comments

1. Where exposure to chemicals, solvents or high pressure wash is anticipated, Mactac recommends sealing the edges with varnish, silicone or other sealant to prevent penetration by these liquids.
 2. Prints should not be applied onto dusty, dirty, oily or oxidized surfaces.
 3. The mounting board must be properly prepared prior to mounting the image. This may include wiping with alcohol, light sanding or surface sealing depending on the board. Contact your board supplier for their recommendation.
 4. Mactac's pressure sensitive mounting films are intended for "Cold Roll Lamination" (50°F - 120°F). The addition of heat while simultaneous mounting with Thermal Overlaminates may result in curl or have other detrimental effects on the finished product.
 5. Whenever possible, always test first to ensure end-use capability.
- *Values given are typical and are not necessarily for use in specification.*

- ® Permacolor is a registered trademark of Morgan Adhesives Company LLC
- ® Fome-Cor is a registered trademark of Monsanto Company.
- ® Gatorfoam is a registered trademark of Alcan, Inc.
- ® Crescent is a registered trademark of the Crescent Cardboard Company.
- ® Masonite is a registered trademark of Masonite Corp.
- ® Sintra is a registered trademark of Alcan Metal, Inc.

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC
® Registered Trademark of Morgan Adhesives Company LLC
www.Mactac.com



www.digitalcolorink.com
877-616-8600
Baltimore, MD | Charlotte, NC