



# Classic Matte 165 165SML

## Matte Lightblock Roll-Up Polyester Film

### Applications

- Roll-up displays

### Benefits

- Premium roll-up material - grey back, 98% opacity
- Anti-reflective, matte, bright-white front surface
- Optimum ink adhesion, fast drying
- Scratch and water resistant
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

### Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

### Recommended Conditions:

Printroom	59°F - 85°F 15°C - 30°C	30% - 65% RH
Usage	50°F - 17°F 10°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

### Printability:

**(Eco) Solvent** ✓✓✓

**Latex** ✓✓✓

**UV** ✓✓✓

### Thickness:

**165** **6.5** **234**  
μ mil gsm

### Available widths:

**914** **1067**  
36" 42"

**1270** **1524**  
50" 60"



Digital  
Color INK

[www.digitalcolorink.com](http://www.digitalcolorink.com)

877-616-8600

Baltimore, MD | Charlotte, NC