



# IconiK 200 200KTB

## Textured Black Polyester Film

### Applications

- Roll-up
- Point of sale, displays

### Benefits

- Perfect black film
- Textured Satin Jet Black with anti-static properties
- Optimum contrast with white inks
- Printable on both sides
- Weather, scratch and water resistant
- No need to laminate

### Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

### Recommended Conditions:

Printroom	59°F - 86°F 15°C - 30°C	30% - 65% RH
Usage	-40°F- 176°F -40°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

Printability:

**(Eco) Solvent** NO

**Latex** NO

**UV** ✓✓✓

Thickness:

**195** **7.7** **210**  
μ mil gsm

Available widths:

**914** **1270** **1524**  
36" 50" 60"



Digital  
Color INK

[www.digitalcolorink.com](http://www.digitalcolorink.com)

877-616-8600

Baltimore, MD | Charlotte, NC