



Ultimate 230 230STL

Textured Lightblock Roll-Up Polyester Film

Applications

- Roll-up displays

Benefits

- Premium Roll-up material - grey back, 98% opacity
- Textured, anti-reflective bright-white front surface
- Scratch and water resistant
- No need for lamination
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

Certified for
HP Latex Inks

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Recommended Conditions:

Printroom	59°F - 86°F 15°C - 30°C	30% - 65% RH
Usage	40°F - 176°F -40°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

Printability:

(Eco) Solvent ✓✓✓

Latex ✓✓✓

UV ✓✓✓

Thickness:

230 μ 9.1 mil 305 gsm

Available widths:

914 36" 1270 50" 1524 60"



www.digitalcolorink.com

877-616-8600

Baltimore, MD | Charlotte, NC