

The PerformanceJet 2508UF




4' x 8' Flatbed UV-LED Printer

The Mutoh PerformanceJet 2508UF 4'x8' UV-LED Flatbed printer excels in performance quality and value. It's standard staggered four print head design - field upgradable to eight heads, provides high print speeds and the dual UV lamps on both sides of the carriage provide exceptional cure times allowing for higher production capacity. Print media up to 4" thick and use the CMYK x2 or CMYK plus white & varnish to create stunning applications with outstanding durability and color gamut. The PJ 2508UF comes standard with an automatic media registration pin system with "blow back" feature for easier handling and positioning of media, an anti-static elimination system and an auto media thickness detector. The PerformanceJet 2508UF delivers outstanding output you expect and provides the reliability you need in a UV-LED flatbed making it the smart choice for any production shop.

www.digitalcolorink.com
877-616-8600
Baltimore, MD | Charlotte, NC



ANATOMY OF A PERFORMANCEJET 2508UF



| | |
|----------------------------------|---|
| Print method | Drop-On Demand, Piezo Drive Method |
| # of nozzles | 1280 (4X320 Channels / 4 heads) |
| # of print heads | 4 default - field upgradeable to 6 or 8 |
| Ink type | UV-LED |
| Media Handling System | 4 Zone Vacuum Table Auto Media Registration Pin System |
| Media Handling System 2 | "Blow Back" Feature to easily slide media across table. |
| Print modes | 600X300 / 600X600 / 600X900 / 600X1200 (dpi) * |
| Color options | CMYK x2 or CMYK, White + Varnish |
| Maximum print speed / resolution | 968 sqft/hr (600X300 / 2 pass / 4 color / 4 head) |
| Maximum Resolution | 600 x 1200 dpi |
| Maximum Print Height | 4 inches (100mm) |
| Maximum media weight | 92.15 lbs. / sq yd. |

| | |
|--------------------------------|----------------------------------|
| Maximum print Area | 100" X 49.2" |
| Variable dot | Yes |
| Curing system | UV-LED Lamp |
| Auto Media Thickness Detection | Included |
| Anti Static Elimination | Included |
| RIP software | Mutoh Edition Flexi Sign & Print |
| Power requirements | 200 - 220VAC MAIN, 50/60Hz, 25A |
| Operating temperature | 68°F - 86°F |
| Operating humidity range | 40% - 70% (non condensing) |
| Dimensions (printer) WxDxH | 186.6" x 78.7" x 56.7" |
| Printer weight | 2,646 lbs |
| Limited warranty | TBA |

*Actual print mode specifications are 605 X 300 / 605 X 600 / 605 X 900 / 605 X 1200 dpi



POP Displays



Packaging



Industrial



Directional

- ✓ UV-LED is an environmentally friendly ink type.
- ✓ Create labels, textured signs and limitless promotional items and much more.
- ✓ Use the blow back feature to easily handle heavier media across the table.
- ✓ Print up to a 4 (100mm)" thick, perfect for promotional items and packaging prototypes.
- ✓ Scale your print head configuration with your business. Field upgradeable up to 6 or 8 heads!

Free Print Sample

www.mutoh.com
1-800-99MUTOH

Easy Financing options with

MUTOH
FINANCIAL SERVICES



Digital
Color ink
TRUSTED KNOWLEDGE PROVEN RESULTS

MUTOH[®]

Specifications Subject to Change

